

Figure 8 Truck Racing Rules at Sigourney

First and for most KEEP IT SIMPLE!!

Safety

1. Must have roll over protection
 - Roll bar must have kickers to the rear
 - On regular cab pickups roll over protection can be external
 - On extended cab pickups the roll over bar must be within a foot (minimum) behind the driver's seat
2. Must have a 5 point safety harness that is secularly fastened!
 - Can be used with racing seat or bench seat
3. Must wear helmets, fire suits and neck brace!
4. Remove all glass, trim, mirrors, headlights, and taillights
5. Windshield must be screened, but no more than half way.
6. Driver door window must have protection to keep driver safe
7. Doors must be securely fastened
8. Drivers door must be adequately reinforced to techs standards
9. Gas tanks have to be in the truck bed and need to be securely fastened and can be no bigger than seven gallon

Rules

1. Chassy needs to be completely stock
2. Full size 2 wheel drive pickups only!
 - 4 wheel drive pickups must have front drive shaft removed
3. **ABSOLUTLY NO RACING SHOCKS!!**
 - Replacement parts must be stock and all parts located in original position
4. Under hood must BE and LOOK stock!
5. Must be a 1 legger (spin 1 rear tire)
6. Tires must be 6 ply and up
7. Tred on tires cannot have more than quarter inch gap on most common tred pattern
8. NO bars in front of radiator
9. Existing gas tanks can either be removed or must have multiple 1 inch or bigger holes punched in them.
10. Battery must be in a box out of the engine compartment
11. Must have a stock box
 - No flat beds or utility boxes
12. Must have stock bumpers and must be bolted on
13. Can only have stock tailgates that need to be welded shut. If no tailgate, box sides may be gusseted at rear with no more than quarter inch angle iron

In the end the techs have the final say. If you do not meet their standards you will be asked to load up your pickup and will be unable to race.

Last but not least, this is supposed to be fun!!